

Chassis Mount Displays Color LCD Flat Panels

Engineered Solutions

As display technologies evolve, so do our customer's imaginations. Pixelink continues to lead the way in engineering solutions to meet the diverse needs of the display marketplace. Whether your application is for a kiosk, CRT replacement, HMI, POS, Public Information Display or Digital Signage, this is the simple all-in-one solution for you. Easily integrated, we combine performance and quality with the versatility of an open frame chassis mountable product. Select from a wide variety of optional touch screens, protective glass, films or privacy shields. Pixelink custom designs and builds for OEM's, providing custom enclosures, private label products, display selection assistance, SBC selection and integration, special power requirements and customized warranty and service programs.



- **A-Si Active Matrix TFT Color LCD Panel**
- **VGA and DVI connections, optional NTSC/PAL, S-Video**
- **Lightweight but rugged design**
- **Superb Quality - clear, bright, high contrast ratio with wide viewing angle**
- **Detects the sync type (separate, composite or sync on green) automatically**
- **Perfect for VARs, System Integrators and OEM's**
- **Optional Touch Screens - Capacitive, Resistive or SAW**
- **Available with Protective Shields (AR/AG or Clear) or Privacy Shields**



Franchised Distributor

eComp®
Electronic Components, Inc.

Phone: 877-GO-eComp
(877-463-2667)
Fax: 508-861-0113
www.ecompbiz.com
sales@ecompbiz.com



Specifications – Chassis Mount Displays

Series	PL150X-CM-XXXR	PL170X-CM-XXXR	PL190X-CM-XXXR
LCD Size	15.0"	17.0"	19.0"
Standard Resolution	1024 x 768	1280 x 1024	1280 x 1024
Pixel Pitch	0.297 mm	0.264 mm	0.294 mm
Pixel Arrangement	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe
Brightness (typical)	250 cd/m ²	300 cd/m ²	300 cd/m ²
Contrast Ratio	500:1	800:1	1300:1
Aspect Ratio	4:3	4:3	4:3
Response Time (typical)	12 ms	7 ms	20 ms
Viewable Area	304.128 mm (H) x 228.096 mm (V)	337.920 mm (H) x 270.336 mm (V)	376.32 mm (H) x 301.056 mm (V)
Horizontal Viewing Angle	130°	160°	178°
Vertical Viewing Angle	120°	160°	178°
Color Depth	16.2 Million	16.2 Million	16.7 Million
Input Signal	Analog	Analog	Analog and DVI
Input Connector	15Pin D-Sub, Optional NTSC/PAL, S-Video, DVI	15Pin D-Sub, Optional NTSC/PAL, S-Video, DVI	15Pin D-Sub, Optional NTSC/PAL, S-Video
Frequency Range	30KHz - 80KHz (H) 50Hz - 75Hz (V)	30KHz - 80KHz (H) 50Hz - 75Hz (V)	30KHz - 80KHz (H) 50Hz - 75Hz (V)
Power Supply Input (external)	DC 12V, 100 - 240V, 50 - 60Hz	DC 12V, 100 - 240V, 50 - 60Hz	DC 12V, 100 - 240V, 50 - 60Hz
Power Supply Output (external)	12V @ 3.5A	12V @ 4.16A	12V @ 4.16A
Power Consumption	12VDC @ 2.0A	12VDC @ 3.0A	12VDC @ 3.0A
Lamp Life	50,000 Hours	50,000 Hours	50,000 Hours
Operating Environment	0°C - 50°C	0°C - 50°C	0°C - 50°C
Relative Humidity	8% - 90% non-condensing	8% - 90% non-condensing	8% - 90% non-condensing
Storage Environment	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C
Relative Humidity	8% - 90% non-condensing	8% - 90% non-condensing	8% - 90% non-condensing
Operating Altitude	10,000 Feet	10,000 Feet	10,000 Feet
Storage Altitude	30,000 Feet	30,000 Feet	30,000 Feet
Dimensions (WxHxD)	15.41" x 11.73" x 1.60"	16.43" x 13.16" x 1.67"	16.77" x 14.05" x 1.80"
Gross Weight	6.3 lbs	9.8 lbs	10.2 lbs
Color	Black or Custom	Black or Custom	Black or Custom
Warranty	1 Year	1 Year	1 Year



Comprehensive Technical Support

- 24X7 Internet and phone service
- Multiple on-site options
- Installation and problem resolution
- Consulting, training and maintenance

Learn more at teklink.rell.com



Franchised Distributor

eComp®
Electronic Components, Inc.

Phone: 877-GO-eComp
(877-463-2667)

Fax: 508-861-0113
www.ecompbiz.com
sales@ecompbiz.com

